



DFT® Inc
 140 Sheree Blvd. PO Box 566
 Exton, PA 19341-0566
Phone: 800.206.4013
Fax: 847.540.1422
Email: dft@dft-valves.com
Website: www.dft-valves.com



Basic-Check® Threaded In-Line Check Valves

The DFT® Basic-Check® Valve is a versatile all-purpose, non-slam valve that provides reliable, low-maintenance service for a wide range of liquids, steam and gases at various pressure/temperature combinations. The valve consists of a guard cage, spring, valve disc, retaining ring and seat. It can be combined with pipe fittings such as reducing couplings, drain elbows, etc. to form a complete check valve unit ideally suited for a broad range of pipeline applications or incorporated into [+ more](#)










1

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8028</u>	0.25 in	0.25 in	1.00 in	BSE	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS	N/A	N/A





Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8001-98</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/TFE®-Viton®		N/A
<u>8057</u>	0.25 in	0.25 in	1.00 in	BSSH6	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8012</u>	0.25 in	0.25 in	1.00 in	BS316S	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8020</u>	0.25 in	0.25 in	1.00 in	BSSH7	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8001-57</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/EPDM		N/A




0.6 psi

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8001X</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.041 bar 16.7 in.water	303 SS		N/A
<u>8001</u>	0.25 in	0.25 in	1.00 in	BSS	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS	N/A	N/A
<u>8001-49</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Buna		N/A
<u>8001-54</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Zelon®		N/A
<u>8001-51</u>	0.25 in	0.25 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Viton®		N/A
<u>8002-98</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/TFE®-Viton®		N/A




Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8002-57</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/EPDM		N/A
<u>8058</u>	0.38 in	0.38 in	1.00 in	BSSH6	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8013</u>	0.38 in	0.38 in	1.00 in	BS316S	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8021</u>	0.38 in	0.38 in	1.00 in	BSSH7	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8002-54</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Zelon®		N/A






0.6 psi




Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8002</u>	0.38 in	0.38 in	1.00 in	BSS	0 psig 2500 psig	0.041 bar 16.7 in.water	303 SS	N/A	N/A
<u>8029</u>	0.38 in	0.38 in	1.00 in	BSE	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS	N/A	N/A
<u>8002X</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS		N/A
<u>8002-51</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Viton®		N/A
<u>8002-49</u>	0.38 in	0.38 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Buna		N/A
<u>8066-54</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.24 psi 0.017 bar 16.7 in.water	303 SS/Zelon®		N/A






Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8066-57</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.24 psi 0.017 bar 16.7 in.water	303 SS/EPDM		N/A
<u>8066-49</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.24 psi 0.017 bar 16.7 in.water	303 SS/Buna		N/A
<u>8066-51</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.24 psi 0.017 bar 16.7 in.water	303 SS/Viton®		N/A
<u>8022</u>	0.5 in	0.50 in	1.00 in	BSSH7	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8014</u>	0.5 in	0.50 in	1.00 in	BS316S	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A





0.24 psi




Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8066-98</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.017 bar 16.7 in.water	303 SS/TFE®-Viton®		N/A
<u>8059</u>	0.5 in	0.50 in	1.00 in	BSSH6	0 psig 6000 psig	0.6 psi 0.041 bar 16.7 in.water	316 SS	N/A	N/A
<u>8066</u>	0.5 in	0.50 in	1.00 in	BSS	0 psig 2500 psig	0.24 psi 0.017 bar 16.7 in.water	303 SS	N/A	N/A
<u>8003X</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS		N/A
<u>8003-49</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Buna		N/A
<u>8030</u>	0.5 in	0.50 in	1.00 in	BSE	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS	N/A	N/A






Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8003</u>	0.5 in	0.50 in	1.00 in	BSS	0 psig 2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS	N/A	N/A
<u>8003-57</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/EPDM		N/A
<u>8003-98</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/TFE®-Viton®		N/A
<u>8003-51</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Viton®		N/A
<u>8003-54</u>	0.5 in	0.50 in	1.00 in	BSS	2500 psig	0.6 psi 0.041 bar 16.7 in.water	303 SS/Zelon®		N/A
<u>8060-51</u>	0.75 in	0.75 in	1.50 in	BSSH6	5500 psig	0.44 psi 0.03 bar 12.1	316 SS/Viton®		N/A


Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
						in.water			
<u>8060-49</u>	0.75 in	0.75 in	1.50 in	BSSH6	5500 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS/Buna		N/A
<u>8060</u>	0.75 in	0.75 in	1.50 in	BSSH6	0 psig 5500 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS	N/A	N/A
<u>8060-54</u>	0.75 in	0.75 in	1.50 in	BSSH6	5500 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS/Zelon®		N/A
<u>8015</u>	0.75 in	0.75 in	1.50 in	BS316S	0 psig 2000 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS	N/A	N/A
<u>8023</u>	0.75 in	0.75 in	1.50 in	BSSH7	0 psig 6000 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS	N/A	N/A
<u>8060-57</u>	0.75 in	0.75 in	1.50 in	BSSH6	5500 psig	0.44 psi 0.03 bar 12.1 in.water	316 SS/EPDM		N/A

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8004-98</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS/TFE®-Viton®		N/A
<u>8004X</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS		N/A
<u>8004</u>	0.75 in	0.75 in	1.50 in	BSS	0 psig 2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS	N/A	N/A
<u>8031</u>	0.75 in	0.75 in	1.50 in	BSE	0 psig 2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS	N/A	N/A
<u>8004-49</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS/Buna		N/A
<u>8004-57</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS/EPDM		N/A
<u>8004-54</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS/Zelon®		N/A





Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8004-51</u>	0.75 in	0.75 in	1.50 in	BSS	2000 psig	0.44 psi 0.03 bar 12.1 in.water	303 SS/Viton®		N/A
<u>8061-51</u>	1 in	1.00 in	2.00 in	BSSH6	3000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS/Viton®		N/A
<u>8061-49</u>	1 in	1.00 in	2.00 in	BSSH6	3000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS/Buna		N/A
<u>8061</u>	1 in	1.00 in	2.00 in	BSSH6	0 psig 3000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS	N/A	N/A
<u>8061-54</u>	1 in	1.00 in	2.00 in	BSSH6	3000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS/Zelon®		N/A
<u>8016</u>	1 in	1.00 in	2.00 in	BS316S	0 psig 1500 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS	N/A	N/A




Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
						in.water			
<u>8024</u>	1 in	1.00 in	2.00 in	BSSH7	0 psig 6000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS	N/A	N/A
<u>8061-57</u>	1 in	1.00 in	2.00 in	BSSH6	3000 psig	0.36 psi 0.025 bar 10.1 in.water	316 SS/EPDM		N/A
<u>8005-98</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS/TFE®-Viton®		N/A
<u>8005X</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS		N/A
<u>8005</u>	1 in	1.00 in	2.00 in	BSS	0 psig 1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS	N/A	N/A
						0.36 psi			






Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8032</u>	1 in	1.00 in	2.00 in	BSE	0 psig 1500 psig	0.025 bar 10.1 in.water	303 SS	N/A	N/A
<u>8005-49</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS/Buna		N/A
<u>8005-57</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS/EPDM		N/A
<u>8005-54</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS/Zelon®		N/A
<u>8005-51</u>	1 in	1.00 in	2.00 in	BSS	1500 psig	0.36 psi 0.025 bar 10.1 in.water	303 SS/Viton®		N/A
<u>8006-57</u>	1.25 in	1.25 in	2.50 in	BSS	850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS/EPDM		N/A




Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8006-54</u>	1.25 in	1.25 in	2.50 in	BSS	850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS/Zelon®		N/A
<u>8062</u>	1.25 in	1.25 in	2.50 in	BSSH6	0 psig 1100 psig	0.16 psi 0.011 bar 4.5 in.water	316 SS	N/A	N/A
<u>8017</u>	1.25 in	1.25 in	2.50 in	BS316S	0 psig 850 psig	0.16 psi 0.011 bar 4.5 in.water	316 SS	N/A	N/A
<u>8025</u>	1.25 in	1.25 in	2.50 in	BSSH7	0 psig 4000 psig	0.16 psi 0.011 bar 4.5 in.water	316 SS	N/A	N/A
<u>8006</u>	1.25 in	1.25 in	2.50 in	BSS	0 psig 850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS	N/A	N/A





0.16 psi

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8009</u>	1.25 in	1.25 in	2.50 in	BSA	0 psig 850 psig	0.011 bar 4.5 in.water	416 SS	N/A	N/A
<u>8006X</u>	1.25 in	1.25 in	2.50 in	BSS	850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS		N/A
<u>8006-51</u>	1.25 in	1.25 in	2.50 in	BSS	850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS/Viton®		N/A
<u>8006-49</u>	1.25 in	1.25 in	2.50 in	BSS	850 psig	0.16 psi 0.011 bar 4.5 in.water	303 SS/Buna		N/A
<u>8063</u>	1.5 in	1.50 in	3.00 in	BSSH6	0 psig 900 psig	0.15 psi 0.01 bar 4.2 in.water	316 SS	N/A	N/A
<u>8007-98</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS/TFE®-Viton®		N/A





Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8026</u>	1.5 in	1.50 in	3.00 in	BSSH7	0 psig 2700 psig	0.15 psi 0.01 bar 4.2 in.water	316 SS	N/A	N/A
<u>8010</u>	1.5 in	1.50 in	3.00 in	BSA	0 psig 700 psig	0.15 psi 0.01 bar 4.2 in.water	416 SS	N/A	N/A
<u>8018</u>	1.5 in	1.50 in	3.00 in	BS316S	0 psig 700 psig	0.15 psi 0.01 bar 4.2 in.water	316 SS	N/A	N/A
<u>8007-57</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS/EPDM		N/A
<u>8007X</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS		N/A
<u>8007</u>	1.5 in	1.50 in	3.00 in	BSS	0 psig 700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS	N/A	N/A
<u>8007-49</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS/Buna		N/A



Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8007-54</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS/Zelon®		N/A
<u>8007-51</u>	1.5 in	1.50 in	3.00 in	BSS	700 psig	0.15 psi 0.01 bar 4.2 in.water	303 SS/Viton®		N/A
<u>8064-51</u>	2 in	2.00 in	4.00 in	BSSH6	450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS/Viton®		N/A
<u>8064-49</u>	2 in	2.00 in	4.00 in	BSSH6	450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS/Buna		N/A
<u>8064</u>	2 in	2.00 in	4.00 in	BSSH6	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS	N/A	N/A
<u>8064-54</u>	2 in	2.00 in	4.00 in	BSSH6	450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS/Zelon®		N/A

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8019</u>	2 in	2.00 in	4.00 in	BS316S	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS	N/A	N/A
<u>8027</u>	2 in	2.00 in	4.00 in	BSSH7	0 psig 800 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS	N/A	N/A
<u>8064-57</u>	2 in	2.00 in	4.00 in	BSSH6	450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS/EPDM		N/A
<u>8008-98</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/TFE®-Viton®		N/A
<u>8008X</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS		N/A
<u>8008</u>	2 in	2.00 in	4.00 in	BSS	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS	N/A	N/A

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
						in.water			
<u>8011</u>	2 in	2.00 in	4.00 in	BSA	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	416 SS	N/A	N/A
<u>8008-49</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Buna		N/A
<u>8008-57</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/EPDM		N/A
<u>8008-54</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Zelon®		N/A
<u>8008-51</u>	2 in	2.00 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Viton®		N/A

0.1 psi

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8000-98</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.007 bar 2.6 in.water	303 SS/TFE®-Viton®		N/A
<u>8000-57</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/EPDM		N/A
<u>8090</u>	2.5 in	2.50 in	4.00 in	BSSH7	0 psig 800 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS	N/A	N/A
<u>8065</u>	2.5 in	2.50 in	4.00 in	BSSH6	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	316 SS	N/A	N/A
<u>8000-54</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Zelon®		N/A
<u>8000X</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS		N/A

Prod. #	Size	Line Size Inlet (FNPT) A	Outside Thread (MNPT) B	Style	Cold Working Pressure	Valve Cracking Pressure	Seat	CAD Download	Inventory
<u>8000</u>	2.5 in	2.50 in	4.00 in	BSS	0 psig 450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS	N/A	N/A
<u>8000-51</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Viton®		N/A
<u>8000-49</u>	2.5 in	2.50 in	4.00 in	BSS	450 psig	0.1 psi 0.007 bar 2.6 in.water	303 SS/Buna		N/A